

<b>DESCRIPTION</b>	Fast Dry Blockout White is a high opacity, solvent reducible alkyd graphic arts primer designed to “block out” previously painted sign faces. This material dries quickly with a flat finish and prepares the surface for the application of Bulletin Colors, background enamels or artist’s oil colors. Fast Dry Block White is also an excellent primer for wood and MDO board.
<b>RECOMMENDED USES</b>	Block out old bulletins or pictorials and prime the surface so that new signs or artwork will adhere and cover properly. BFDDBO also provides the proper surface for carbon pouncing or felt tip layouts.
<b>SURFACE PREPARATION</b>	<p>All surfaces must be clean, free from loose or peeling paint, grease, oil, dirt, rust, mill scale and other contaminants. If this procedure is not observed, the drying and adhesion of any coating will be adversely affected.</p> <p><b>Previously Painted Surfaces:</b> Dull gloss areas by light sanding to enhance adhesion.</p> <p><b>Wood Surfaces:</b> Clean surface to eliminate oil, grease and other contaminants.</p> <p><b>MDO Plywood:</b> Clean surface to eliminate oil, grease and other contaminants. Prime face with Fast Dry Blockout White. Edges should be puttied and then primed with two coats Fast Dry Blockout White.</p>
<b>APPLICATION</b>	<p>Follow surface preparation instructions. Stir thoroughly before use.</p> <p>Use any good quality bristle brush or apply by roller with 1/2” lambs wool or 1/4 - 1/2” synthetic cover. Keep the roller wet. Roll in one direction, rewet, then cross roll. May also be spray applied. Follow spray gun manufacturer’s recommendations.</p>
<b>THINNING</b>	Do not thin under normal conditions.
<b>CLEAN UP</b>	Mineral Spirits
<b>DRY TIMES</b>	At 70°F and 50% relative humidity, Fast Dry Blockout White will be dry to touch in 30-45 minutes. Wait two (2) hours to handle and three (3) hours to recoat. Wait eight (8) hours for full cure. Dry times may take longer in cooler and/or more humid conditions.
<b>APPLICATION CONDITIONS</b>	Minimum temperature: 50°F Maximum temperature: 95°F Maximum humidity: 90%

# TECHNICAL DATA SHEET—PAGE 2

## FAST DRY BLOCKOUT WHITE

<b>FINISH</b>	Flat White
<b>WEIGHT PER GALLON</b>	12.4 lbs (approximate)
<b>SOLIDS %</b>	75% by weight
<b>VISCOSITY</b>	72-80 KU at 75°F
<b>THEORETICAL COVERAGE</b>	Approximately 400 square feet at 4 mils wet
<b>SPREAD RATE</b>	642 square feet @ 1 mil dry
<b>FLASH POINT</b>	105°F
<b>PACKAGING</b>	US Gallon (128 fl oz), 4/case US Quart (32 fl oz), 6/case
<b>STORAGE TEMPERATURE</b>	Minimum: 40°F Maximum: 95°F
<b>SHELF LIFE</b>	Two (2) years
<b>VOC INFO</b>	Varies by color but will not exceed 450 grams/liter
<b>CAUTIONS</b>	Read Safety Data Sheet and/or all warnings on the label before handling or using this product.
<b>PRODUCT WARRANTY</b>	All recommendations for the use of Ronan products are based on tests and experience believed to be reliable. It is the responsibility of the purchaser to determine the suitability of this product for its intended use. Since the methods of use, conditions of application and the application itself are beyond the manufacturer's and seller's control, product warranty is restricted to replacement of defective materials only. No other warranty, written or oral, is expressed or implied.
<b>REVISION DATE</b>	July 1, 2018